

Firestone

Load and Inflation Tables Table of Contents

Medium Truck Tire..... 59

Commercial Light Truck Tire..... 64

Medium Truck
Light Truck
General Technical
Load/Inflation
Technical Bulletins

Medium Truck Tire

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS
Tire Load Limits at various Cold Inflation Pressures. Pressure listed is the MINIMUM for the LOAD.

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits at various Cold Inflation Pressures											
		kPa	480	520	550	590	620	660	690	720	760	790	830
		psi	70	75	80	85	90	95	100	105	110	115	120
9.00R20	DUAL	kg.	1750(D) ¹²⁷	1830	1910	2000(E) ¹³²	2080	2160	2240(F) ¹³⁶	2300	2360	2430(G) ¹³⁹	
		lb.	3860(D)	4045	4230	4410(E)	4585	4760	4940(F)	5080	5220	5355(G)	
	SINGLE	kg.	1850(D) ¹²⁹	1940	2030	2120(E) ¹³⁴	2200	2280	2360(F) ¹³⁸	2430	2500	2575(G) ¹⁴¹	
		lb.	4080(D)	4280	4480	4675(E)	4850	5025	5205(F)	5360	5515	5675(G)	
9.00R20 T546 ONLY	DUAL	kg.	1750	1830	1910	2000	2080	2160	2240	2250(G)			
		lb.	3860	4045	4230	4410	4585	4760	4940	4970(G)			
	SINGLE	kg.	1850	1940	2030	2120	2200	2280	2360	2430	2500	2570(G)	
		lb.	4080	4280	4480	4675	4850	5025	5205	5360	5515	5670(G)	
10.00R20	DUAL	kg.	1990	2080	2160	2250	2360(F) ¹³⁸	2460	2560	2650(G) ¹⁴²	2680	2710	2725(H) ¹⁴³
		lb.	4380	4580	4760	4950	5205(F)	5415	5625	5840(G) ¹⁴²	5895	5950	6005(H) ¹⁴³
	SINGLE	kg.	2050	2160	2260	2370	2500(F) ¹⁴⁰	2600	2700	2800(G) ¹⁴⁴	2870	2940	3000(H) ¹⁴⁶
		lb.	4530	4770	4990	5220	5510(F)	5730	5950	6175(G) ¹⁴⁴	6320	6465	6610(H) ¹⁴⁶
10.00R20 T546 Only	DUAL	kg.	1990	2080	2160	2250	2360	2460	2560	2600	2630(H)		
		lb.	4380	4580	4760	4950	5205	5415	5625	5720	5800(H)		
	SINGLE	kg.	2050	2160	2260	2370	2500	2600	2700	2800	2870	2940	3000(H) ¹⁴⁶
		lb.	4530	4770	4990	5220	5510	5730	5950	6175	6320	6465	6610(H) ¹⁴⁶
11.00R20	DUAL	kg.	2170	2260	2360	2450	2575(F) ¹⁴¹	2630	2680	2725(G) ¹⁴³	2840	2960	3075(H) ¹⁴⁷
		lb.	4780	4990	5190	5390	5675(F)	5785	5895	6005(G) ¹⁴³	6265	6525	6780(H) ¹⁴⁷
	SINGLE	kg.	2240	2360	2470	2580	2725(F) ¹⁴³	2820	2910	3000(G) ¹⁴⁶	3120	3240	3350(H) ¹⁵⁰
		lb.	4940	5200	5450	5690	6005(F) ¹⁴³	6205	6405	6610(G) ¹⁴⁶	6870	7130	7390(H) ¹⁵⁰
12.00R20	DUAL	kg.	2470	2580	2680	2790	2880	3000(G) ¹⁴⁶	3080	3160	3250(H) ¹⁴⁹	3350	3450(J) ¹⁵¹
		lb.	5440	5680	5910	6140	6360	6610(G) ¹⁴⁶	6790	6970	7160(H) ¹⁴⁹	7390	7610(J) ¹⁵¹
	SINGLE	kg.	2550	2690	2810	2940	3060	3250(G) ¹⁴⁹	3350	3450	3550(H) ¹⁵²	3650	3750(J) ¹⁵⁴
		lb.	5620	5920	6200	6480	6740	7160(G) ¹⁴⁹	7380	7600	7830(H) ¹⁵²	8050	8270(J) ¹⁵⁴
11.00R22	DUAL	kg.	2300	2400	2500	2600	2650(F) ¹⁴²	2770	2890	3000(G) ¹⁴⁶	3080	3160	3250(H) ¹⁴⁹
		lb.	5080	5300	5520	5730	5840(F)	6095	6350	6610(G) ¹⁴⁶	6790	6970	7160(H) ¹⁴⁹
	SINGLE	kg.	2380	2500	2630	2740	2900(F) ¹⁴⁵	3020	3140	3250(G) ¹⁴⁹	3350	3450	3550(H) ¹⁵²
		lb.	5240	5520	5790	6040	6395(F)	6650	6910	7160(G) ¹⁴⁹	7380	7600	7830(H) ¹⁵²

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.
International Load Index numbers are shown after Load Range.
IMPORTANT- ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	kPa	550	590	620	660	690	720	760	790	830	860	900
		psi	80	85	90	95	100	105	110	115	120	125	130
315/80R22.5	Dual	kg.	2575	2650	2750	2900	2970	3070	3150	3270	3450(J) ¹⁵¹	3560	3750(L)
		lb.	5675	5840	6070	6395	6545	6770	6940	7210	7610(J) ¹⁵¹	7850	8255(L)
	Single	kg.	2800	2910	3030	3150	3260	3370	3450	3590	3750(J) ¹⁵⁴	3900	4080(L)
		lb.	6175	6415	6670	6940	7190	7440	7610	7920	8270(J) ¹⁵⁴	8600	9000(L)
315/80R22.5 FS400 & T819	Dual	kg.	2575	2650	2750	2900	2970	3070	3150	3270	3450(J) ¹⁵¹	3560	3750(L) ¹⁵⁴
		lb.	5675	5840	6070	6395	6545	6770	6940	7210	7610(J) ¹⁵¹	7850	8270(L) ¹⁵⁴
	Single	kg.	2800	2910	3030	3150	3260	3370	3450	3590	3750(J) ¹⁵⁴	3900	4125(L) ¹⁵⁷
		lb.	6175	6415	6670	6940	7190	7440	7610	7920	8270(J) ¹⁵⁴	8600	9090(L) ¹⁵⁷

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.
International Load Index numbers are shown after Load Range.
IMPORTANT- ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Medium Truck Tire

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (kPa/psi) Pressure Listed is the Minimum for the Load											
		kPa	480	520	550	590	620	660	690	720	760	790	830
		psi	70	75	80	85	90	95	100	105	110	115	120
8R19.5	DUAL	kg.	1120	1170	1215(D) ₁₁₅	1285	1310	1360(E) ₁₁₉	1410	1460	1500(F) ₁₂₂		
		lb.	2460	2570	2680(D) ₁₁₅	2785	2890	3000(E) ₁₁₉	3100	3200	3305(F) ₁₂₂		
	SINGLE	kg.	1150	1220	1285(D) ₁₁₇	1340	1400	1450(E) ₁₂₁	1500	1550	1600(F) ₁₂₄		
		lb.	2540	2680	2835(D) ₁₁₇	2955	3075	3195(E) ₁₂₁	3305	3415	3525(F) ₁₂₄		
8R22.5	DUAL	kg.	1250	1300	1360(D) ₁₁₉	1410	1460	1500(E) ₁₂₂	1570	1640	1700(F) ₁₂₆		
		lb.	2750	2870	3000(D) ₁₁₉	3100	3200	3305(E) ₁₂₂	3455	3605	3750(F) ₁₂₆		
	SINGLE	kg.	1290	1360	1450(D) ₁₂₁	1500	1550	1600(E) ₁₂₄	1670	1740	1800(F) ₁₂₈		
		lb.	2840	2990	3195(D) ₁₂₁	3305	3415	3525(E) ₁₂₄	3675	3825	3970(F) ₁₂₈		
9R22.5	DUAL	kg.	1480	1550	1610	1670	1750(E) ₁₂₇	1820	1890	1950(F) ₁₃₁	2010	2070	2120(G) ₁₃₄
		lb.	3270	3410	3550	3690	3860(E) ₁₂₇	4005	4150	4300(F) ₁₃₁	4425	4550	4675(G) ₁₃₄
	SINGLE	kg.	1530	1610	1690	1760	1850(E) ₁₂₉	1920	1990	2060(F) ₁₃₃	2120	2180	2240(G) ₁₃₆
		lb.	3370	3560	3730	3890	4080(E) ₁₂₉	4235	4390	4540(F) ₁₃₃	4675	4810	4940(G) ₁₃₆
10R22.5	DUAL	kg.	1750	1830	1910	2000(E) ₁₃₂	2080	2160	2240(F) ₁₃₈	2300	2360	2430(G) ₁₃₉	
		lb.	3860	4045	4230	4410(E) ₁₃₂	4585	4760	4940(F) ₁₃₈	5075	5210	5350(G) ₁₃₉	
	SINGLE	kg.	1850	1940	2030	2120(E) ₁₃₄	2200	2280	2360(F) ₁₃₈	2430	2500	2575(G) ₁₄₁	
		lb.	4080	4280	4480	4675(E) ₁₃₄	4850	5025	5205(F) ₁₃₈	5360	5515	5675(G) ₁₄₁	
11R22.5	DUAL	kg.	1990	2080	2160	2250	2360(F) ₁₃₈	2460	2560	2650(G) ₁₄₂	2680	2710	2725(H) ₁₄₃
		lb.	4380	4580	4760	4950	5205(F) ₁₃₈	5415	5625	5840(G) ₁₄₂	5895	5950	6005(H) ₁₄₃
	SINGLE	kg.	2050	2160	2260	2370	2500(F) ₁₄₀	2600	2700	2800(G) ₁₄₄	2870	2940	3000(H) ₁₄₆
		lb.	4560	4770	4990	5220	5510(F) ₁₄₀	5730	5950	6175(G) ₁₄₄	6320	6465	6610(H) ₁₄₆
11R24.5	DUAL	kg.	2110	2210	2300	2390	2500(F) ₁₄₀	2580	2660	2725(G) ₁₄₃	2820	2910	3000(H) ₁₄₆
		lb.	4660	4870	5070	5260	5510(F) ₁₄₀	5675	5840	6005(G) ₁₄₃	6205	6405	6610(H) ₁₄₆
	SINGLE	kg.	2190	2300	2410	2520	2650(F) ₁₄₂	2770	2890	3000(G) ₁₄₆	3080	3160	3250(H) ₁₄₉
		lb.	4820	5070	5310	5550	5840(F) ₁₄₂	6095	6350	6610(G) ₁₄₆	6790	6970	7160(H) ₁₄₉
12R22.5	DUAL	kg.	2170	2260	2350	2440	2575(F) ₁₄₁	2630	2680	2725(G) ₁₄₃	2840	2960	3075(H) ₁₄₇
		lb.	4780	4990	5190	5390	5675(F) ₁₄₁	5785	5895	6005(G) ₁₄₃	6265	6525	6780(H) ₁₄₇
	SINGLE	kg.	2240	2360	2470	2580	2725(F) ₁₄₃	2820	2910	3000(G) ₁₄₆	3120	3240	3350(H) ₁₅₀
		lb.	4940	5000	5450	5690	6005(F) ₁₄₃	6205	6405	6610(G) ₁₄₆	6870	7130	7390(H) ₁₅₀
12R24.5	DUAL	kg.	2300	2400	2500	2600	2650(F) ₁₄₂	2770	2890	3000(G) ₁₄₆	3080	3160	3250(H) ₁₄₉
		lb.	5080	5300	5520	5730	5840(F) ₁₄₂	6095	6350	6610(G) ₁₄₆	6790	6970	7160(H) ₁₄₉
	SINGLE	kg.	2380	2500	2630	2740	2900(F) ₁₄₅	3020	3140	3250(G) ₁₅₂	3350	2450	3550(H) ₁₅₂
		lb.	5240	5520	5790	6040	6395(F) ₁₄₅	6650	6910	7160(G) ₁₅₂	7380	7600	7830(H) ₁₅₂

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS AND CONTOURS.

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits at Various Cold Inflation Pressures											
		kPa	590	620	660	690	720	760	790	830	860	900	930
		psi	85	90	95	100	105	110	115	120	125	130	135
9R17.5HC	DUAL	kg.	1380	1430	1480	1520	1600(F) ₁₂₄	1650	1700	1750(G) ₁₂₇	1800	1850	1900(H) ₁₃₀
		lb.	3040	3150	3260	3360	3525(F) ₁₂₄	3635	3745	3860(G) ₁₂₇	3970	4080	4190(H) ₁₃₀
	SINGLE	kg.	1450	1520	1570	1630	1700(F) ₁₂₆	1750	1800(G) ₁₃₃	1850(G) ₁₂₉	1900	1950	2000(H) ₁₃₂
		lb.	3200	3340	3470	3590	3750(F) ₁₂₆	3860	3970(G) ₁₃₃	4080(G) ₁₂₉	4190	4300	4410(H) ₁₃₂
10R17.5HC	DUAL	kg.	1650(E) ₁₂₅	1720	1790	1850(F) ₁₂₉	1920	1990	2060(G) ₁₃₃				
		lb.	3640(E) ₁₂₅	3785	3930	4080(F) ₁₂₉	4235	4390	4540(G) ₁₃₃				
	SINGLE	kg.	1750(E) ₁₂₇	1820	1890	1950(F) ₁₃₁	2030	2110	2180(G) ₁₃₅				
		lb.	3860(E) ₁₂₇	4005	4150	4300(F) ₁₃₁	4470	4640	4805(G) ₁₃₅				

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT- ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Firestone

Medium Truck Tire

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES, AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures (psi) Pressure Listed is the Minimum for the Load											
		kPa	480	520	550	590	620	660	690	720	760	790	830
		psi	70	75	80	85	90	95	100	105	110	115	120
245/75R22.5	DUAL	kg.	1430	1500	1600	1640	1710	1800	1840	1900	1950(G) ¹³¹		
		lb.	3160	3315	3525	3615	3765	3970	4055	4195	4300(G)		
	SINGLE	kg.	1570	1650	1750	1800	1880	1950	2020	2090	2120(G) ¹³⁴		
		lb.	3470	3645	3860	3975	4140	4300	4455	4610	4675(G)		
265/75R22.5	DUAL	kg.	1600	1680	1750	1830	1910	2000	2050	2130	2180(G) ¹³⁵		
		lb.	3525	3705	3860	4040	4205	4410	4525	4685	4805(G)		
	SINGLE	kg.	1760	1850	1950	2010	2100	2180	2260	2340	2360(G) ¹³⁸		
		lb.	3875	4070	4300	4440	4620	4805	4975	5150	5205(G)		
295/75R22.5	DUAL	kg.	1860	1950	2060	2130	2220	2300(F) ¹³⁷	2390	2470	2575(G) ¹⁴¹	2630	2725(H) ¹⁴³
		lb.	4095	4300	4540	4690	4885	5070(F)	5260	5440	5675(G)	5795	6005(H)
	SINGLE	kg.	2040	2140	2240	2340	2440	2500(F) ¹⁴⁰	2620	2710	2800(G) ¹⁴⁴	2890	3000(H) ¹⁴⁸
		lb.	4500	4725	4940	5155	5370	5510(F)	5780	5980	6175(G)	6370	6610(H)
285/75R24.5	DUAL	kg.	1870	1970	2060	2150	2240	2360(F) ¹³⁸	2410	2490	2575(G) ¹⁴¹	2660	2800(H) ¹⁴⁴
		lb.	4135	4340	4540	4740	4930	5205(F)	5310	5495	5675(G)	5860	6175(H)
	SINGLE	kg.	2060	2160	2240	2360	2460	2575(F) ¹⁴¹	2650	2740	2800(G) ¹⁴⁴	2920	3075(H) ¹⁴⁷
		lb.	4545	4770	4940	5210	5420	5675(F)	5835	6040	6175(G)	6640	6780(H)

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.
International Load Index numbers are shown after the Load Range.
IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

METRIC WIDE BASE RADIAL TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES ARE USED AS SINGLES

TIRE SIZE DESIGNATION	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
	kPa	480	520	550	590	620	660	690	720	760	790	830
	psi	70	75	80	85	90	95	100	105	110	115	120
445/50R22.5	kg.			3330	3520	3660	3850	3990	4130	4310	4450	4625
	lb.			7370	7740	8100	8460	8820	9170	9515	9860	10200
445/65R19.5	kg.	3410	3610	3750	3960	4100	4250	4410	4540	4750(J) ¹⁶²		
	lb.	7540	7930	8270	8680	9040	9370	9730	10100	10500(J)		
385/65R22.5	kg.	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4750(L) ¹⁶²
	lb.	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370(L)
425/65R22.5	kg.	3430	3640	3750	3980	4130	4250	4440	4580	4750(J) ¹⁶²	4880	5150(L) ¹⁶²
	lb.	7590	7990	8270	8740	9100	9370	9370	10100	10500(J)	10700	11400(L)
445/65R22.5	kg.	3720	3950	4125	4320	4470	4625	7820	4960	5150	5290	5600(L) ¹⁶²
	lb.	8230	8660	9090	9480	9870	10200	10600	11000	11400	11700	12300(L)

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.
International Load Index numbers are shown after the Load Range.
IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Medium Truck Tire

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (kPa/psi) Pressure Listed is the Minimum for the Load												
		kPa	480	520	550	590	620	660	690	720	760	790	830	860
		psi	70	75	80	85	90	95	100	105	110	115	120	125
215/75R17.5 FS560+ ONLY	DUAL	kg. lb.			1450 3195	1520 3350	1590 3500	1650 3645	1720 3795	1790 3945	1860 4095	1910 4220	1990 4390	2060(H) 4540(H) ¹³⁵
	SINGLE	kg. lb.			1530 3375	1610 3540	1680 3695	1750 3860	1820 4010	1900 4180	1960 4330	2040 4495	2110 4650	2180(H) 4805(H) ¹⁴³
225/70R19.5	DUAL	kg. lb.	1230 2720	1300 2860	1360(E) 3000(E) ¹¹⁹	1410 3115	1470 3245	1550(F) 3415(F) ¹²³	1580 3490	1640 3615	1700(G) 3750(G) ¹²⁶			
	SINGLE	kg. lb.	1310 2895	1380 3040	1450(E) 3195(E) ¹²¹	1500 3315	1570 3450	1650(F) 3640(F) ¹²⁵	1690 3715	1740 3845	1800(G) 3970(G) ¹²⁸			
245/70R19.5 FS560+ ONLY	DUAL	kg. lb.			1550 3415	1590 3515	1660 3655	1750(F) 3860(F) ¹²⁷	1790 3940	1850 4075	1985(G) 4375(G)			
	SINGLE	kg. lb.			1650 3640	1700 3740	1770 3890	1850(F) 4080(F) ¹²⁹	1900 4190	1970 4335	2060(G) 4545(G) ¹³³			
265/70R19.5	DUAL	kg. lb.			1700 3745	1780 3925	1860 4100	1950 4300	2000 4405	2005 4415	2120(G) 4675(G) ¹³⁴			
	SINGLE	kg. lb.			1800 3970	1900 4180	1970 4355	2060 4540	2130 4685	2200 4850	2300(G) 5070(G) ¹³⁷			
285/70R19.5	DUAL	kg. lb.				1980 4365	2000 4400	2120 4675	2150 4735	2220 4900	2300(G) 5070(G) ¹³⁷	2380 5255	2570 5675	2725(H) 6005(H) ¹⁴³
	SINGLE	kg. lb.				2110 4645	2190 4835	2300 5070	2360 5205	2440 5385	2500(G) 5510(G) ¹⁴⁰	2600 5740	2800 6175	2900(H) 6395(H) ¹⁴⁵
305/70R19.5	DUAL	kg. lb.			2060 4540	2120 4670	2200 4860	2300 5070	2370 5230	2450 5410	2575(H) 5675(H) ¹⁴¹	2620 5770	2725 6005	2900(J) 6395(J) ¹⁴⁵
	SINGLE	kg. lb.			2240 4940	2330 5130	2420 5340	2500 5510	2610 5745	2700 5945	2800(H) 6175(H) ¹⁴⁴	2870 6340	3000 6610	3150(J) 6945(J) ¹⁴⁸
255/70R22.5	DUAL	kg. lb.			1800 3970	1860 4110	1940 4275	2000 4410	2020 4455	2090 4610	2120(G) 4675(G) ¹³⁴	2230 4915	2300(H) 5070(H) ¹³⁷	
	SINGLE	kg. lb.			1900 4190	1980 4370	2060 4550	2120 4675	2220 4895	2300 5065	2360(G) 5205(G) ¹³⁸	2450 5400	2500(H) 5510(H) ¹⁴⁰	
275/70R22.5	DUAL	kg. lb.				2080 4590	2180 4815	2290 5040	21390 5270	2490 5490	2590 5720	2690 5940	2900(H) 6395(H) ¹⁴⁵	
	SINGLE	kg. lb.				2230 4920	2340 5160	2450 5400	2560 5645	2670 5880	2780 6130	2890 6365	3175(H) 7000(H)	
275/80R22.5	DUAL	kg. lb.			2060 4540	2130 4690	2220 4885	2300(F) 5070(F) ¹³⁷	2390 5260	2470 5440	2575(G) 5675(G) ¹⁴¹	2630 5795	2725(H) 6005(H) ¹⁴³	
	SINGLE	kg. lb.			2240 4940	2340 5155	2440 5370	2500(F) 5510(F) ¹⁴⁰	2620 5780	2710 5980	2800(G) 6175(G) ¹⁴⁴	2890 6370	3000(H) 6610(H) ¹⁴⁶	
295/80R22.5	DUAL	kg. lb.			2180 4810	2300 5080	2420 5340	2540 5600	2660 5860	2780 6130	2900 6390	3075 780	3115 6860	3150(H) 6940(H) ¹⁴⁸
	SINGLE	kg. lb.			2430 2430	2560 2560	2690 2690	2820 6220	2950 6510	3090 6810	3220 7100	3350 3350	3455 7610	3550(H) 7830(H) ¹⁵²
305/75R22.5	DUAL	kg. lb.			2360 5205	2440 5375	2540 5595	2560 5840	2730 6025	2830 6235	3000(H) 6610(H) ¹⁴⁶	3010 6640	3150(J) 6940(J) ¹⁴⁸	
	SINGLE	kg. lb.			2575 5675	2680 5905	2790 6150	2900 6395	3000 6620	3110 6850	3250(H) 7160(H) ¹⁴⁹	3310 7300	3450(J) 7610(J) ¹⁵¹	
305/85R22.5	DUAL	kg. lb.			2430 5355	2520 5550	2620 5780	2725 6005	2820 6215	2920 6435	3075(H) 6780(H) ¹⁴⁷			
	SINGLE	kg. lb.			2650 840	2770 6100	2880 6350	3000 6610	3100 6830	3210 7070	3350(H) 7390(H) ¹⁵⁰			
305/75R24.5	DUAL	kg. lb.			2170 4780	2290 5040	2400 5300	2520 5560	2660 5860	2640 5820	2760 6090	2880 6340	3010 6640	3150(H) 6945(H) ¹⁴⁸
	SINGLE	kg. lb.			2380 5251	2510 5540	2640 5820	2770 6110	2900 6400	3030 6680	3160 6970	3290 7260	3420 7540	3550(H) 7830(H) ¹⁵²

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.
International Load Index numbers are shown after Load Range.
IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Medium Truck Tire

RADIAL PLY METRIC TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (kg./lb.) at various Cold Inflation Pressures (kPa/psi) Pressure Listed is the Minimum for the Load											
		kPa	480	520	550	590	620	660	690	720	760	790	830
		psi	70	75	80	85	90	95	100	105	110	115	120
245/75R22.5	DUAL	kg.	1430	1500	1600	1640	1710	1800	1840	1900	1950(G) ¹³¹		
		lb.	3160	3315	3525	3615	3765	3970	4055	4195	4300(G)		
	SINGLE	kg.	1570	1650	1750	1800	1880	1950	2020	2090	2120(G) ¹³⁴		
		lb.	2470	3645	3860	3975	4140	4300	4455	4610	4675(G)		
265.75R22.5	DUAL	kg.	1600	1680	1750	1830	1910	2000	2050	2130	1950(G) ¹³¹		
		lb.	3523	3705	3860	4040	4205	4410	4525	4525	4300(G)		
	SINGLE	kg.	1760	1850	1950	2010	2100	2180	2260	2340	2360(G) ¹³⁸		
		lb.	3875	4070	4300	4440	4620	4805	4975	5150	5206(G)		
295/75R22.5	DUAL	kg.	1860	1950	2060	2130	2220	2300(F) ¹³⁷	2390	2470	2575(G) ¹⁴¹	2630	2725(H) ¹⁴³
		lb.	4095	4300	4540	4690	4885	5070(F)	5260	5440	5675(G)	5795	6005(H)
	SINGLE	kg.	2040	2140	2240	2340	2440	2500(F) ¹⁴⁰	2620	2710	2800(G) ¹⁴⁴	2890	3000(H) ¹⁴⁸
		lb.	4500	4725	4940	5155	5370	5510(F)	5780	5980	6175(G)	6370	6610(H)
295/75R22.5 R227 ONLY	DUAL	kg.	1860	1950	2060	2130	2220	2300(F) ¹³⁷	2390	2470	2575(G) ¹⁴¹	2870	3000(H) ¹⁴⁸
		lb.	4095	4300	4540	4690	4885	5070(F)	5260	5440	5675(G)	6330	6610(H)
	SINGLE	kg.	2040	2140	2240	2340	2440	2500(F) ¹⁴⁰	2620	2710	2800(G) ¹⁴⁴	3150	3250(H) ¹⁴⁹
		lb.	4500	4725	4940	5155	5370	5510(F)	5780	5980	6175(G)	6950	7160(H)
285/75R24.5	DUAL	kg.	1870	1970	2060	2150	2240	2360(F) ¹³⁸	2410	2490	2575(G) ¹⁴¹	2660	2800(H) ¹⁴⁴
		lb.	4135	4340	4540	4740	4930	5205(F)	5310	5495	5675(G)	5860	6175(H)
	SINGLE	kg.	2060	2160	2240	2360	2460	2575(F) ¹⁴¹	2650	2740	2800(G) ¹⁴⁴	2920	3075(H) ¹⁴⁷
		lb.	4545	4770	2240	2360	2460	5675(F)	5835	6040	6175(G)	6440	6780(H)

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT - ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Commercial Light Truck Tire

LIGHT TRUCK METRIC TIRES FOR TRUCKS, BUSES, TRAILERS AND MULTI-PURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE

RADIAL PLY TIRES MOUNTED ON 5° DROP CENTER RIMS									
TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures							
		kPa	250	300	350	400	450	500	550
		psi	35	45	50	60	65	75	80
LT205/75R15	DUAL	kg.	530	605	690(C) ⁹⁵	740	800(D) ¹⁰⁰		
		lb.	1145	1360	1520(C)	1665	1765(D)		
	SINGLE	kg.	585	665	750(C) ⁹⁸	815	875(D) ¹⁰³		
		lb.	1260	1500	1655(C)	1795	1930(D)		
LT215/75R15	DUAL	kg.	570	645	730(C) ⁹⁷	790	875(D) ¹⁰³		
		lb.	1255	1420	1610(C)	1740	1930(D)		
	SINGLE	kg.	625	710	800(C) ¹⁰⁰	870	950(D) ¹⁰⁶		
		lb.	1375	1565	1765(C)	1915	2095(D)		
LT225/75R15	DUAL	kg.	610	690	775(C) ⁹⁹	845	900(D) ¹⁰⁴		
		lb.	1345	1520	1710(C)	1860	1985(D)		
	SINGLE	kg.	670	760	850(C) ¹⁰²	930	1000(D) ¹⁰⁸		
		lb.	1475	1675	1875(C)	2050	2205(D)		
LT235/75R15	DUAL	kg.	645	735	825(C) ¹⁰¹	900	975(D) ¹⁰⁷	1060	1150(E) ¹¹³
		lb.	1420	1620	1820(C)	1985	2150(D)	2335	2535(E)
	SINGLE	kg.	710	810	900(C) ¹⁰⁴	990	1060(D) ¹¹⁰	1160	1250(E) ¹¹⁶
		lb.	1565	1785	1985(C)	2180	2335(D)	2555	2755(E)
LT245/75R15	DUAL	kg.	690	785	875(C) ¹⁰³				
		lb.	1520	1730	1930(C)				
	SINGLE	kg.	760	865	975(C) ¹⁰⁷				
		lb.	1675	1905	2150(C)				
LT255/75R15	DUAL	kg.	735	835	925(C) ¹⁰⁵				
		lb.	1620	1840	2040(C)				
	SINGLE	kg.	805	915	1030(C) ¹⁰⁹				
		lb.	1775	2015	2270(C)				
LT265/75R15	DUAL	kg.	780	885	1000(C) ¹⁰⁸				
		lb.	1720	1950	2205(C)				
	SINGLE	kg.	855	970	1090(C) ¹¹¹				
		lb.	1885	2140	2405(C)				

NOTES: Letters in parentheses () denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown after the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.

Firestone

Commercial Light Truck Tire

LIGHT TRUCK METRIC TIRES FOR TRUCKS, BUSES, TRAILERS AND
MULTIPURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE.
RADIAL PLY TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits at various Cold Inflation Pressures										
		kPa	250	280	310	350	380	410	450	480	520	550
		psi	35	40	45	50	55	60	65	70	75	80
80 SERIES												
LT215/80R15	DUAL	kg.	590	645	675	750	810	825	875(D) ₁₀₃			
		lb.	1275	1395	1515	1655	1745	1855	1930(D)			
	SINGLE	kg.	650	710	740	825	890	905	975(D) ₁₀₇			
		lb.	1400	1535	1665	1820	1920	2040	2150(D)			
LT235/80R17	DUAL	kg.	730	800	830	925	1015	1010	1120	1090	1180	1285(E) ₁₁₇
		lb.	1570	1725	1870	2040	2190	2315	2470	2560	2685	2835(E)
	SINGLE	kg.	800	880	910	1030	1115	1110	1215	1305	1300	1400(E) ₁₂₀
		lb.	1725	1895	2055	2270	2405	2545	2680	2815	2950	3085(E)
85 SERIES												
LT215/85R16	DUAL	kg.	630	690	720	800(C) ₁₀₀	865	870	975(D) ₁₀₇	1025	1030	1120(E) ₁₁₂
		lb.	1360	1490	1625	1765(C)	1865	1985	2150(D) ₁₀₇	2210	2320	2470(E)
	SINGLE	kg.	695	760	790	880(C) ₁₀₃	950	965	1060(D) ₁₁₀	1130	1130	1215(E) ₁₁₅
		lb.	1495	1640	1785	1940(C) ₁₀₃	2050	2180	2335(D) ₁₁₀	2430	2550	2680(E)
LT235/85R16	DUAL	kg.	720	790	820	910(C) ₁₀₄	985	1000	1080(D) ₁₁₁	1165	1170	1260(E) ₁₁₆
		lb.	1545	1700	1845	2006(C)	2125	2260	2381(D) ₁₁₁	2515	2645	2778(E)
	SINGLE	kg.	790	965	900	1000(C) ₁₀₈	1100	1155	1190(D) ₁₁₄	1285	1290	1380(E) ₁₂₀
		lb.	1700	1870	2030	2205(C) ₁₀₈	2335	2485	2623(D) ₁₁₄	2765	2905	3042(E)
LT255/85R16	DUAL	kg.	815	890	930	1030(C) ₁₀₉	1115	1130	1250(D) ₁₁₆	1320	1320	1400(E) ₁₂₀
		lb.	1745	1920	2085	2270(C) ₁₀₉	2400	2550	2755(D) ₁₁₆	2840	2980	3085(E)
	SINGLE	kg.	895	980	1020	1120(C) ₁₁₂	1225	1240	1360(D) ₁₁₉	1450	1450	1550(E) ₁₂₃
		lb.	1920	2110	2290	2470(C) ₁₁₂	2635	2800	3000(D) ₁₁₉	3120	3275	3415(E)

NOTES: Letters in parentheses () denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown after the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.

RADIAL PLY TIRES FOR TRUCKS, BUSES, TRAILERS IN NORMAL HIGHWAY SERVICE
MOUNTED ON FLAT BASE RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits at various Cold Inflation Pressures									
		kPa	410	450	480	520	550	590	620	660	690
		psi	60	65	70	75	80	85	90	95	100
7.50R16LT	DUAL	kg.	925	975(D) ₁₀₇	1020	1065	1120(E) ₁₁₂	1150	1190	1250(F) ₁₁₆	1450(G) ₁₂₁
		lb.	2040	2150(D)	2245	2345	2470(E)	2540	2630	2755(F)	3195(G)
	SINGLE	kg.	1050	1120(D) ₁₁₂	1160	1210	1250(E) ₁₁₆	1310	1360	1400(F) ₁₂₀	1510(G) ₁₂₂
		lb.	2310	2470(D)	2560	2670	2755(E)	2885	2900	3085(F)	3330(G)

NOTES: Letters in parentheses () denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown after the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.

Commercial Light Truck Tire

LIGHT TRUCK METRIC TIRES FOR TRUCKS, BUSES, TRAILERS AND MULTI-PURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE.
RADIAL PLY TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures										
		kPa	250	275	300	350	380	400	450	780	500	550
		psi	35	40	45	50	55	60	65	70	75	80
LT225/75R16	DUAL	kg.	635	675	725	800(C) ¹⁰⁰	945	885	975(D) ¹⁰⁷	1000	1040	1120(E) ¹¹²
		lb.	1365	1500	1630	1765(C)	1875	1995	2150(D)	2220	2330	2470(E)
	SINGLE	kg.	700	745	795	880(C) ¹⁰³	930	970	1060(D) ¹¹⁰	1100	1140	1215(E) ¹¹⁵
		lb.	1500	1650	1790	1940(C)	2060	2190	2335(D)	2440	2560	2680(E)
LT245/75R16	DUAL	kg.	720	765	820	910(C) ¹⁰⁴	960	1000	1080(D) ¹¹¹	1135	1170	1260(E) ¹¹⁶
		lb.	1545	1695	1845	2006(C)	2125	2255	2381(D)	2515	2640	2778(E)
	SINGLE	kg.	790	840	900	1000(C) ¹⁰⁸	1055	1100	1190(D) ¹¹⁴	1250	1290	1380(E) ¹²⁰
		lb.	1700	1865	2030	2205(C)	2335	2480	2623(D)	2765	2900	3042(E)
LT265/75R16	DUAL	kg.	810	860	920	1030(C) ¹⁰⁹	1080	1130	1250(D) ¹¹⁶	1275	1310	1400(E) ¹²⁰
		lb.	1740	1910	2075	2270(C)	2390	2540	2755(D)	2825	2965	3085(E)
	SINGLE	kg.	890	950	1010	1120(C) ¹¹²	1185	1240	1360(D) ¹¹⁹	1400	1440	1550(E) ¹²³
		lb.	1910	2100	2280	2470(C)	2625	2790	3000(D)	3105	3260	3415(E)
LT285/75R16	DUAL	kg.	900	960	1030	1150(C) ¹¹³	1200	1260	1360(D) ¹¹⁹			
		lb.	1940	2130	2310	2535(C)	2660	2830	3000(D)			
	SINGLE	kg.	990	1055	1130	1250(C) ¹¹⁶	1320	1380	1500(D) ¹²²			
		lb.	2130	2340	2540	2755(C)	2925	3110	3305(D)			

NOTES: Letters in parentheses denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown above the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

LIGHT TRUCK METRIC TIRES FOR TRUCKS, BUSES, TRAILERS AND MULTI-PURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits at various Cold Inflation Pressures										
		kPa	250	275	300	350	380	400	450	780	500	550
		psi	35	40	45	50	55	60	65	70	75	80
LT245/70R17	DUAL	kg.	715	810	810	900(C) ¹⁰⁴	955	990	1060(D) ¹¹⁰	1135	1160	1250(E) ¹¹⁶
		lb.	1540	1830	1830	1985(C)	2105	2240	2335(D)	2495	2615	2755(E)
	SINGLE	kg.	785	840	890	1000(C) ¹⁰⁸	1050	1090	1180(D) ¹¹⁴	1240	1270	1360(E) ¹¹⁹
		lb.	1690	1855	2010	2205(C)	2315	2460	2600(D)	2740	2875	3000(E)
LT265/70R17	DUAL	kg.	800	855	910	1030(C) ¹⁰⁹	1070	110	1215(D) ¹¹⁵	1240	1260	1320(E) ¹¹⁸
		lb.	1720	1890	2050	2270(C)	2360	2510	2680(D)	2735	2820	2910(E)
	SINGLE	kg.	880	940	100	1120(D) ¹¹²	1175	1220	1320(D) ¹¹⁸	1360	1390	1450(E) ¹²¹
		lb.	1890	2075	2255	2470(D)	2595	2760	2910(D)	3005	3100	3195(E)
LT245/75R17	DUAL	kg.	750	800	855	925	1040	1070	1150	1195	1220	1320(E) ¹¹⁶
		lb.	1610	1770	1920	2040	2210	2360	2535	2640	2775	2910(E)
	SINGLE	kg.	825	880	935	1030	1100	1140	1250	1315	1340	1450(E) ¹²¹
		lb.	1770	1945	2110	2270	2430	2595	2755	2900	3050	3195(E)
LT275/65R18	DUAL	kg.	820	880	930	1060(C) ¹¹⁰	1095	1140	1250	1300	1130	1400(E) ¹²⁰
		lb.	1765	1940	2110	2335(C)	2420	2570	2755	2865	3010	3085(E)
	SINGLE	kg.	880	965	1045	1150(C) ¹¹³	1205	1250	1360	1425	1450	1550(E) ¹²³
		lb.	1940	2130	2310	2535(C)	2660	2825	3000	3150	3305	3415(E)
LT275/70R18	DUAL	kg.	875	935	990	1120	1175	1220	1320	1390	1420	1500(E) ¹²²
		lb.	1885	2065	2250	2470	2585	2750	2910	3060	3210	3305(E)
	SINGLE	kg.	960	1030	1090	1215	1290	1340	1450	1525	1560	1650(E) ¹²⁵
		lb.	2070	2270	2470	2680	2840	3020	3195	3360	3530	3640(E)

NOTES: Letters in parentheses denote Load Range for which boldface loads are MAXIMUM.

International Load Index numbers are shown above the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETER AND CONTOURS.

Commercial Light Truck Tire

LIGHT TRUCK TIRES FOR TRUCKS, BUSES, TRAILERS AND MULTIPURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE
TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	RADIAL PLY													
		kPa	250	280	310	350	380	410	450	480	520	550	590	620	660
		psi	35	40	45	50	55	60	65	70	75	80	85	90	95
		DIAGONAL (BIAS) PLY													
		kPa	210	250	280	310	350	380	410	450	480	520	550	590	620
psi	30	240	40	45	50	55	60	65	70	75	80	85	90		
8.00*16.5LT	DUAL	kg.	540	595	640	690(C) ⁹⁵	735	775	825(D) ¹⁰¹	855	895	925(E) ¹⁰⁵	965	1000	1030(F) ¹⁰⁵
		lb.	1195	1310	1415	1520(C)	1620	1710	1820(D)	1885	1970	2040(E)	2130	2200	2270(F)
	SINGLE	kg.	615	675	730	800(C) ¹⁰⁰	835	880	925(D) ¹⁰⁵	975	1020	1060(E) ¹¹⁰	1100	1130	1180(F) ¹¹⁴
		lb.	1360	1490	1610	1765(C)	1840	1945	2040(D)	2145	2240	2335(E)	2420	2500	2600(F)
8.75*16.5LT	DUAL	kg.	625	685	740	800(C) ¹⁰⁰	840	895	950(D) ¹⁰⁵	985	1030	1090(E) ¹¹¹	1110	1150	1215(F) ¹¹⁵
		lb.	1380	1515	1630	1765(C)	1855	1970	2095(D)	2175	2260	2405(E)	2450	2540	2680(F)
	SINGLE	kg.	710	780	840	900(C) ¹⁰⁴	955	1020	1090(D) ¹¹¹	1120	1170	1215(E) ¹¹⁵	1260	1310	1360(F) ¹¹⁹
		lb.	1570	1720	1850	1985(C)	2110	2240	2405(D)	2470	2570	2680(E)	2780	2880	3000(F)
9.50*16.5LT	DUAL	kg.	740	810	875	950(C) ¹⁰⁶	1000	1060	1120(D) ¹¹²	1170	1220	1285(E) ¹¹⁷			
		lb.	1635	1785	1925	2095(C)	2200	2330	2470(D)	2570	2685	2835(E)			
	SINGLE	kg.	845	920	995	1090(C) ¹¹¹	1130	1200	1285(D) ¹¹⁷	1320	1380	1450(E) ¹²¹			
		lb.	1860	2030	2190	2405(C)	2500	2650	2835(D)	2920	3050	3195(E)			
10*16.5LT	DUAL	kg.	730(B) ⁹⁷	805	865	925(C) ¹⁰⁵	990	1050	1120(D) ¹¹²	1150	1200	1250(E) ¹¹⁶			
		lb.	1610(B)	1770	1910	2040(C)	2180	2310	2470(D)	2540	2650	2755(E)			
	SINGLE	kg.	850(B) ¹⁰²	910	985	1060(C) ¹¹⁰	1120	1190	1250(D) ¹¹⁸	1310	1370	1450(E) ¹²¹			
		lb.	1875(B)	2010	2170	2335(C)	2480	2620	2755(D)	2885	3010	3195(E)			
12*16.5LT	DUAL	kg.	950(C) ¹⁰⁶	1030	1120	1215(D) ¹¹⁶	1270	1350	1450(E) ¹²¹	1490	1550	1650(F) ¹²⁵			
		lb.	2095(C)	2280	2460	2680(D)	2810	2970	3195(E)	3275	3420	3640(F)			
	SINGLE	kg.	1090(C) ¹¹¹	1170	1270	1360(D) ¹¹⁹	1450	1530	1650(E) ¹²⁵	1690	1760	1850(F) ¹²⁹			
		lb.	2405(C)	2590	2800	3000(D)	3190	3370	3640(E)	3720	3885	4080(F)			

NOTES: Letters in parentheses () denote Load Range for which boldface loads are MAXIMUM

International Load Index numbers are shown after the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.

LIGHT TRUCK TIRES FOR TRUCKS, BUSES, TRAILER, AND MULTIPURPOSE PASSENGER VEHICLES USED IN NORMAL HIGHWAY SERVICE
RADIAL PLY TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures										
		RADIAL PLY										
		kPa	250	280	310	340	380	410	450	480	520	550
		psi	35	40	45	50	55	60	65	70	75	80
		DIAGONAL (BIAS) PLY										
		kPa	210	240	280	310	340	380	410	450	480	520
		psi	30	35	40	45	50	55	60	65	70	75
6.50*16LT	DUAL	kg.	510	555	600	650(C) ₈₃	680	720	750(D) ₈₈	795	830	875(E) ₁₀₃
		lb.	1120	1225	1320	1435(C)	1500	1590	1655(D)	1750	1830	1930(E)
	SINGLE	kg.	575	630	680	730(C) ₈₇	775	815	875(D) ₁₀₃	905	945	975(E) ₁₀₇
		lb.	1270	1390	1500	1610(C)	1710	1800	1930(D)	1990	2080	2150(E)
6.70*15LT	DUAL	kg.	480	530	575	615(C) ₈₁	655	690	730(D) ₈₇	760	795	825(E) ₁₀₁
		lb.	1060	1170	1265	1355(C)	1440	1520	1610(D)	1670	1750	1820(E)
	SINGLE	kg.	550	600	650	690(C) ₈₅	740	780	825(D) ₁₀₁	860	900	925(E) ₁₀₅
		lb.	1210	1320	1430	1530(C)	1630	1720	1820(D)	1900	1980	2040(E)
7.00*15LT	DUAL	kg.	540	595	645	690(C) ₈₅	735	780	825(D) ₁₀₁	850	890	925(E) ₁₀₅
		lb.	1190	1310	1420	1520(C)	1620	1715	1820(D)	1870	1960	2040(E)
	DUAL	kg.	610	670	730	775(D) ₈₉	830	880	925(D) ₁₀₅	965	1005	1060(E) ₁₁₀
		lb.	1350	1480	1610	1710(C)	1830	1940	2040(D)	2130	2220	2335(E)

NOTES: Letters in parentheses () denote Load Range for which boldface loads are MAXIMUM

International Load Index numbers are shown after the Load Range.

IMPORTANT: ALWAYS USE APPROVED TIRE AND RIM COMBINATIONS FOR DIAMETERS AND CONTOURS.